

UHF Long Range -DL6810



Specification:

DL6810 UHF Long Range Reader Reader.Important performance	
Support protocol	ISO18000-6B/ISO18000-6C(EPC G2)
Working frequency	ISM 902MHz~928MHz,Or 920MHz~925MHz
customization	860MHz~960MHz
Working mode	FHSS or working mode of fixed frequency pulse transmitting set by software
Transmit power	20dBm~30 dBm(set by software)
DL6810 UHF Long Range Reader Reader.Read-Write performance	
Read speed	The average read time for single card is less than 10ms per 64 bits
Read distance	8m~15m(according of tag and entironment)
Write speed	8bits less than 30ms
Write distance	4m~7m(according tag)
Read prompt	Buzzer
DL6810 UHF Long Range Reader Reader.Data Port interface	
DL6810A	RS-232 + RS-485 + Wiegand26/34
DL6810B	RS-232 + RS-485 + Wiegand + USB
DL6810C	RS-232 + Wiegand + Ethernet
DL6810 UHF Long Range Reader Reader.Electric parameter	
Power supply	DC+5V
Power consumption	5W
DL6810 UHF Long Range Reader Reader.Exterior and weight	
Dimension	200mm×190mm×80mm
Weight	1000g
DL6810 UHF Long Range Reader Reader.Working environment	
Working temperature	-30°C~70°C