

Argox OS-214TT (printer)



Argox OS-214TT Barcode Label Printer

TECHNICAL SPECIFICATIONS:

Printing Method	Thermal Transfer and Direct Thermal Printing Modes.
Resolution	203 dpi
Print Speed	1~3"/sec (25.4~76.2 mm/s)
Label Printing Length	Max 45" (1143mm)
Maximum Print Width	4.13"(105mm)
Fonts	International character sets standard 5 alpha- numeric fonts from 0.049" ~ 0.23" H (1.25mm ~ 6.0mm) All fonts are expandable up to 24 x 24 4 direction 0° ~ 270° rotation Windows True Type Fonts are downloadable as Soft Fonts.
Barcode Symbologies	Linear: Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A, B, C) Codabar, Interleave 2 of 5, EAN- 8 2& 5 add on, EAN- 13, EAN- 128, UPC, UPC- A, E 2& 5 add on, POSTNET, German POST, 2D Bar Codes : Matrix 25, Maxicode, PDF- 417
4Memory	512 KB DRAM 512 KB Flash ROM
Data Interface	RS-232 serial, Centronics parallel
Media Sensing	Sensor Location : Fixed Left Aligned Sensor Type : Label gap, Punch Hole, Notch, Black Mark (Reflective) media sensing.
Print Media	Roll- feed, die- cut, continuous, fan- fold, tags, ticket in thermal paper or plain paper Media width : 1.0" (25.4mm) - 4.25" (108mm) Thickness : 0.0025" ~ 0.01" (0.0635mm ~ 0.254mm) Max roll capacity 4.3" (109mm) OD (internal) Core size : Min 1" (25mm) ID

Argox OS-214TT (printer)

Ribbon Specs	Wax, Wax/ Resin, Resin Thermal Transfer Ribbons (Outside coating ribbon) Ribbon width : 4" Max Ribbon roll : max OD 1.45" (37mm) Core size : ID 0.5" core (13mm) with notches.
Image Handling	PCX, bit map, IMG, HEX, GDI graphics.
Software	Argox PPLA/ PPLB Language Windows Driver (Win 98/ 2000/ NT/ XP) Label editing software - ArgoBar Print Utility
Status Indications	2 Bi-Color Led for status and error indication. 1 Function Key
Power	19 VAC or DC24V (min 2.5A) 50/ 60 Hz, External Power Adapter
Environment	Operation: 40° F ~ 100° F (4° C ~ 38° C)
Humidity	Operation: 10~90% non condensing
Cert. Approval	CE, UL, CUL, FCC, CCC
Printer Dimension	Width: 186mm Height: 153mm Length: 278mm Weight: 1.9Kg
Options / Accessories	Cutter Dispenser kit Real time clock card ArgoNet print server External USB connector ArgoKee 2MB Asian Font card (Traditional Chinese, Simplified Chinese, Korean and Japanese)