

Metrologic MS-9520



Metrologic MS-9520

TECHNICAL SPECIFICATIONS:

Light Source:	Visible Laser Diode 650 nm +10 nm
Depth of Field:	0 mm - 203 mm (0" - 8") for 0.33 mm (13 mil) bar codes
Width of Field:	64 mm (2.5") @ face; 249 mm (9.8") @ 203 mm (8")
Scan Speed:	72 ± 2 scan lines per second
Scan Pattern:	Single scan line
Minimum Bar Width:	0.127 mm (5 mil)
Dimensions:	198 mm (7.8") H x 40 mm (1.6") D x Handle Width: 45 mm (1.8") Head Width: 78 mm (3.1")
System Interfaces:	PC Keyboard Wedge, RS232, OCIA, Light Pen Emulation, IBM 468X/469X, Stand Alone Keyboard, USB (low speed and full speed)
Light Source:	Visible Laser Diode 650 nm ± 10 nm
Weight:	149 g (5.25 oz)
Shock:	Designed to withstand 1.5 m (5') drops
Power:	5.2 VDC +0.25 V
Power:	5.2 VDC +0.25 V
EMC	FCC, ICES-003 & EN55022 Class B
Environment:	Operating Temperature: 0 °C to 40 °C (32 °F to 104 °F) Storage Temperature: -40 °C to 60 °C (-40 °F to 140 °F) Humidity: 5% to 95% relative humidity, non-condensing